# **PCT**

# WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



# INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: WO 96/39045 (11) International Publication Number: A23G 1/00 A1 (43) International Publication Date: 12 December 1996 (12.12.96) (21) International Application Number: PCT/US96/04699 (81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, (22) International Filing Date: 5 April 1996 (05.04.96) JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN. (30) Priority Data: US 08/461,430 5 June 1995 (05.06.95) Published With international search report. (71) Applicant: KRAFT FOODS, INC. [US/US]; 250 North Street, White Plains, NY 10625 (US). (72) Inventors: CULLY, Kevin, John; 455 Sunset Terrace, Lake Bluff, IL 60044 (US). CARVALLO, Federico de Loyola; 532 Surf Court, Wheeling, IL 60090 (US). ABDAL-LAH, Qadri, Mustafa; 36923 Oakwood Drive, Lake Villa, IL 60049 (US). GAIM-MARSONER, Gunther, Rudolf; Rouges-Terres 17, CH-2068 Hauterive (CH). (74) Agents: WRIGHT, Debbie, K. et al.; Kraft Foods, Inc., 250 North Street, White Plains, NY 10625 (US).

#### (54) Title: METHOD FOR REDUCING THE VISCOSITY OF CHOCOLATE

#### (57) Abstract

The present invention is directed to a method for reducing the viscosity of melted chocolate. In the method, a chocolate mixture is provided which includes a chocolate source, a fat source and a sweetener. The chocolate mixture is subjected to refining and conching or other processing. Thereafter, the liquified chocolate mixture, which is liquified during conching, is subjected to high shear mixing while the chocolate mixture is still in the molten state.

## FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgystan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic	SD	Sudan
CF	Central African Republic		of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SG	Singapore
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LR	Liberia	SZ	Swaziland
CS	Czechoslovakia	LT	Lithuania	TD	Chad
CZ	Czech Republic	LU	Luxembourg	TG	Togo
DE	Germany	LV	Larvia	TJ	Tajikistan
DK '	Denmark	MC	Monaco	TT	Trinidad and Tobago
EE	Estonia	MD	Republic of Moldova	UÀ	Ukraine
ES	Spain	· MG	Madagascar	UG	Uganda
FI	Finland .	ML	Mali	US	United States of America
FR	France	MN	Mongolia	uz	Uzbekistan
GA	Gabon	MR	Mauritania	VN	Viet Nam

PCT/US96/04699 WO 96/39045

- 1 -

### METHOD FOR REDUCING THE VISCOSITY OF CHOCOLATE

## Field of the Invention

The present invention is directed to a method for reducing the viscosity of melted chocolate. More 5 particularly, the present invention is directed to a method for reducing the viscosity of melted chocolate which results in an improvement in the smoothness of the chocolate. As used herein, the term chocolate means confectionery masses containing cocoa butter and/or other vegetable fats.

## Background of the Invention

10

20

25

The essential components of a conventional chocolate formulation are cocoa "nib", i.e., the roasted cocoa bean with shell and germ removed, sugar and cocoa butter additional to that contained in the nib. Cocoa 15 nib is approximately 50% cocoa butter, the balance being proteins, carbohydrates, tannins, acids, etc. butter content of the chocolate controls its setting characteristics and largely governs its cost, and while the ratio of cocoa nib to sugar determines the type of chocolate, the cocoa butter content varies according to the application. Thus, bitter sweet chocolate has a ratio of nib to sugar of 2:1 while sweet chocolate has a ratio of 1:2. Molding chocolate may have a fat content of 25% to 40%, covering chocolate 33 to 36%, chocolate for hollow goods 38 to 40% and chocolate for covering ice cream 50 to 60%.

The typical preparation of chocolate involves four stages. In the first stage, the ingredients are 30 mixed together in a process which also involves grinding or rubbing, e.g., on a multiple roll press to provide a smooth fluid paste. The ingredients may be added sequentially and in particular the cocoa butter may be added stepwise to control the viscosity of the

- 2 -

composition. The sugar may also be preground to a smaller particle size to reduce the length of time required in the grinding/rubbing of the chocolate mixture. Most chocolate, and certainly all good quality 5 product, is subjected after mixing to the process of "conching" in which the chocolate mixture is subjected to temperature treatment and mechanical working to give the chocolate an improved texture and a fuller and more homogeneous flavor. Other ingredients such as flavors, 10 e.g., vanilla and extra cocoa butter may be added at this stage if desired. A frequently added additional ingredient is lecithin or other emulsifier which improves the flow properties of the chocolate and thereby enables the amount of fat to be reduced. The third stage of the 15 chocolate preparation is called "tempering" in which nuclei are provided in the liquid chocolate composition to facilitate the rapid crystallization of selected stable fat crystals on cooling. The final appearance of the chocolate, its texture and keeping properties depend upon correct tempering stage conditions. After tempering, the chocolate may finally be cast into molds to set or may be used in an enrobing process to produce chocolate coated confectionery, etc.

particular with the conching step, during or after liquification, in the process described in the preceding paragraph. Generally, the drying and liquification steps are performed during conching. The changes taking place during conching are subtle and not completely understood.

What is certain is that the texture of the chocolate is improved and the flavor changed to the extent that without conching the taste of the chocolate is generally commercially unacceptable. The kneading action during the conching process and the maintenance of an elevated temperature together cause evaporation of moisture and volatile acids such as acetic acid, destroy harsh flavors

- 3 -

and reduce astringency, probably due to modification of tannins and the reduction in viscosity.

;

25

There are two stages in the conching operation, a first stage called "dry" conching and a second stage called "liquid" conching. The dry conching process is operated for a period of up to 20 hours at a temperature above 60° C. and usually about 80° C. The extra fat and other ingredients are added towards the end of the conching period, e.g., about one hour before the end of the period. In the liquid conching stage all of the fat and other ingredients such as lecithin are present early in the process to maintain the fluidity of the mass which is mechanically worked for a prolonged time, e.g., 2 or 30 hours or more and at a relatively low temperature, e.g., 40° C. up to 60° C.

Conching procedures and equipment have evolved over the years. Early conches were of the longitudinal type having long marble tubs with raised sides forming a shell. In this shell, an undulating granite roller worked and mixed the chocolate for from 24 to 36 hours. Later, classical mixers were able to reduce conching time to between about 5 to 8 hours by using plow and shear blades to tumble dry refinings in the beginning of dry conching and then, when the mass is plasticized, put energy into the material being conched. Another current rotary conch incorporates a horizontal mixer design which has three shafts with kneading and shearing blades attached. The center blade rotates in one direction and the two outboard shafts rotate the opposite direction, which directions are reversed when desired. These types of horizontal rotary conches provide a so-called "doubleoverthrow" action to thoroughly mix and bring new material into its high shear zones in order to shorten the dry conching cycle time. Scrapers and kneader stirrer arms on the horizontal shafts overlap one

- 4 -

another, providing powerful shearing in the mass and at the walls.

5

10

15

20

25

30

The viscosity of the melted fat after conching increases as the level of fat is reduced. For this reason, enrobing chocolate which requires a high degree of fluidity has the highest level of fat, i.e., about 50% cocoa butter. It would be desirable to provide a method for reducing the viscosity of the melted chocolate after liquification produced during conching or other suitable processing at the lower fat levels to permit lower fat contents to be used in the manufacture of the chocolate. It would also be desirable to provide a method for treating the chocolate to improve the smoothness of the chocolate for better customer acceptance.

Summary of the Invention

The present invention is directed to a method for reducing the viscosity of melted chocolate. In the method, a chocolate mixture is provided which includes a chocolate source, a fat source and a sweetener. The chocolate mixture is subjected to refining and conching or other processing. Thereafter, the liquified chocolate mixture is subjected to high shear mixing while the chocolate mixture is still in the molten state.

#### Detailed Description of the Invention

The method of the present invention is not limited to the production of a chocolate product from any specific starting ingredients, but may be used with any ingredients normally employed, e.g., cocoa powder, chocolate liquor, cocoa butter, and/or other vegetable fats, such as coconut oil and palm kernel oil, sugar and/or sugar replacer, lecithin, etc. Likewise, the process is not limited to the production of any specific type of chocolate product, but is useful for the production of a variety of chocolate products, such as chocolate coatings, sweet chocolate, bittersweet chocolate, milk chocolate, enrobing chocolate, etc.

- 5 -

Since the method of the invention reduces the viscosity of the melted chocolate after the liquification step of conching, it is possible to use levels of fat lower than are normally used in the preparation of chocolate 5 products. The level of total fat in commercial chocolate products is from above about 22%. In the method of the present invention, the total fat level may be reduced by about 3% and in some cases by as much as 10%.

In one embodiment of the present invention, 10 cocoa liquor is combined with the sweetener, usually sucrose and an emulsifier, usually lecithin and other ingredients. This mixture is then subjected to roll refining to reduce the particle size of the cocoa particles, the sugar particles and milk powder, if 15 present. The grittiness of the final chocolate product is dependent upon the size of the particles which are produced during the refining step. It is usually desirable to have very fine particles of less than about 15-50 microns. However, size reduction beyond a certain point results in an increase in viscosity of the 20 chocolate after liquification. Size reduction heretofore has been constrained by such viscosity increase to a larger particle size than desired. In the method of the present invention, however, the viscosity of the 25 liquified chocolate is reduced which means that lower particle sizes can also be used.

The refined cocoa mixture is then combined with cocoa butter or other suitable confectionery fat, such as coconut oil or palm kernel oil prior, during or after liquification during conching. Some of the cocoa butter may be withheld until the end of the conching step. conching step takes place in suitable commercial equipment at a temperature in the range of from about 55° C. to about 80° C.

35 After liquification, the chocolate mixture, while still melted, is subjected to high shear mixing.

30

PCT/US96/04699 WO 96/39045

- 6 -

The temperature of the mixture, which is dependent upon the particular ingredients included therein, i.e., the type of fat moiety, can range between 40° C. - 80° C. For example, a higher melting fat, such as, a more highly saturated fat, like palm oil, requires a higher mixture temperature when processing in the high shear mixer. high shear mixing takes place in suitable apparatus which is sufficient to impart a peak shear of from about 3000 sec'l to about 70,000 sec'l and a shear history of from about 100 to about 20,000. Shear history is a 10 dimensionless number and is a summation of the shear rate times the residence time of the volume of all elements under shear. Suitable high shear mixers include the Dispax<sup>TM</sup> mixer, the Hydroshear<sup>TM</sup> mixer and the Pentax<sup>TM</sup> mixer. The Dispax<sup>TM</sup> mixer is a preferred mixer for reasons of simplicity of operation and design. The Dispax mixer consists of from 1 to 3 stages of rotor/stators mounted in a cylindrical housing. melted chocolate as it passes through the Dispax mixer is 20 forced to flow between the clearance between the rotor and the stator and is sheared during the passage.

The following example further illustrates the method of the invention, but is intended to in no way limit the scope of the invention as set forth in the appended claims.

#### Example 1

Five lots of a milk chocolate composition having the following composition were prepared:

	<u>Ingredient</u>	Weight Percent
30	Cocoa liquor	12.78
	crystallized sugar	44.5%
	added cocoa butter	14.3%
	milk powder	17.5%
	other ingredients	11.0%
35	The ingredients were	ground and mixed t

25

The ingredients were ground and mixed together to form a homogeneous mass while at a temperature of

-7-

35° C. The mixture was then milled on a five roller mill until the desired average particle size of 20 to 40 microns was achieved. The mixture was then conched in a rotary conch for 6 hours at a temperature of 60° C.

5 Additional cocoa butter (about 3.0%) and lecithin (about 0.7%) were added after 4 hours. The chocolate mass, while at a temperature of 45° C. - 55° C. was then processed through a Dispax<sup>TM</sup> mixer containing a single stage of coarse rotor-stators. The results for the 5 lots of chocolate, with respect to viscosity before and after treatment with the high shear mixer are as follows:

Table 1

	Viscosity Reduction	Temperature Rise
15	38%	30
	25%	30
	29%	27
	28%	30
L	27%	19

PCT/US96/04699

#### WHAT IS CLAIMED IS:

1. A method for reducing the viscosity of melted chocolate comprising:

- (a) providing a chocolate mixture comprising a chocolate source selected from the group consisting of cocoa powder and chocolate liquor, a fat source selected from the group consisting of cocoa butter, a vegetable fat and a sweetener;
- (b) subjecting said chocolate mixture to conching; and
- (c) subjecting said conched chocolate mixture to high shear mixing while said chocolate mixture is melted.
- 2. A method in accordance with Claim 1 wherein said high shear mixing imparts a shear rate of from about 3,000 sec<sup>-1</sup> to about 70,000 sec<sup>-1</sup> and a shear history of from about 100 to about 20,000.
- 3. A method in accordance with Claim 1 wherein the total fat of said chocolate is from about 22% to about 50% by weight.
- 4. A method in accordance with Claim 1 wherein at least part of said mixture is subjected to roll refining to reduce the particle size of the cocoa powder and sweetener to particles in the range of from about 15 microns to about 50 microns.

## INTERNATIONAL SEARCH REPORT

International application No. PCT/US96/04699

A. CLASSIFICATION OF SUBJECT MATTER							
IPC(6) :A23G 1/00 US CL :426/660							
According to International Patent Classification (IPC) or to both national classification and IPC							
B. FIELDS SEARCHED							
Minimum documentation searched (cla	assification system follower	d by classification symbols)					
U.S. : 426/660, 659							
	nimum documentation to the	e extent that such documents are included	in the fields searched				
NONE							
Electronic data base consulted during	the international search (na	ame of data base and, where practicable	, search terms used)				
NONE							
C. DOCUMENTS CONSIDERE	D TO BE RELEVANT						
Category* Citation of document	, with indication, where ar	ppropriate, of the relevant passages	Relevant to claim No.				
Y Elements of Foo	d Technology, 19	977, N.W. Desrosier, AVI	1-4				
	Westport, CT, pa	ages 579-587, especially					
page 586.							
Y Chocolate, Co	coa and Confed	ctionery: Science and	1-4				
		W. Minifie, pages 94-103,	1 4				
	ally pages 94, 12						
·							
	•						
		•					
		3					
Further documents are listed in	the continuation of Box C	See patent family annex.					
Special categories of cited document	g:	'T' later document published after the int					
"A" document defining the general state of to be of particular relevance	f the art which is not considered	date and not in conflict with the applic principle or theory underlying the inv	anon but cased to understand the ention				
"E" earlier document published on or after		"X" document of particular relevance; the	e claimed invention cannot be red to involve an inventive step				
"L" document which may throw doubts cited to establish the publication de	on priority claim(s) or which is ate of another citation or other	when the document is taken alone					
special reason (as specified)  *O* document referring to an oral disci		"Y" document of particular relevance; the considered to involve an inventive combined with one or more other suc	step when the document is				
"P" document published prior to the inter		being obvious to a person skilled in t	be art				
the priority date claimed		'&' document member of the same patent					
Date of the actual completion of the in	næmational search	Date of mailing of the international sec	arch report				
19 MAY 1996		<b>07</b> JUN 1996					
Name and mailing address of the ISA	Authorized officer	11.2.111					
Commissioner of Patents and Trademark Box PCT Washington, D.C. 20231	3	Authorized officer ( effect Thomas CAROLYN PADEN )					
Facsimile No. (703) 305-3230		Telephone No. (703) 308-3294					

Form PCT/ISA/210 (second sheet)(July 1992)\*